



Atlantic 2200



VR2200



VRC2200

New Model

Model	VR/VRC2200
VESSEL LENGTH	12 - 15m 38 - 48ft
POWER SUPPLY (DC)	12/24V
MOTOR (Watts)	1200
HYDRAULIC PRESSURE	10MPa 1450PSI
HYDRAULIC FLOW	15L/min 4gal/min
MAX LOAD	1000kg 2200lb
WORK LOAD	250kg 550lb
AMPS WORK LOAD	120/75
MAX LINE SPEED	15m/min 50ft/min
CHAIN SIZE	6 - 8 - 10mm 1/4 - 5/16 - 3/8"
ROPE SIZE	12 - 14 - 16mm 1/2 - 9/16 - 5/8"
NET WEIGHT	DC VR 28kg VRC 29kg HYD VR 26kg VRC 27kg DC VR 61lb VRC 64lb HYD VR 57lb VRC 59lb
MANUAL OPERATION	MOS (opt)

Features

- Rope chain combination gypsy for rope and chain combination or chain only
- Quick release integrated swivel chain pipe cover
- Gypsy with capstan (VRC) or gypsy with low profile clutch top arrangement (VR)
- Heavy duty marine grade, dual direction motor in 12 & 24V DC, Hydraulic
- Luxury chromed finish over marine grade bronze
- Independent gypsy and capstan operation
- Capstan model features heavy duty knurled finish for increased grip
- Self aligning gearbox/adaptor
- Stainless steel shaft
- Cone clutch/brake
- Stainless steel mounting bolts
- Shaft seal
- Lubricating grease nipple
- Clutch release handle
- Installation/Operation booklet



Options

- Rope Chain Management System (RCMS)
- Manual Operation System (MOS)
- Traditional polished bronze finish
- Extra deck clearance kit for any deck thickness
- Full range of accessories including chain, rope, anchors, anchor roller, chain stoppers, snubber kits & devil claws
- Electric & hydraulic operating options & accessories
- Auto anchor

